















This highly versatile floor offers delightful innovation with never-before-seen visuals in fresh, unique colorways. The Uniclic® locking system is milled into all four sides, producing a tight connection that installs quickly. A commercial grade wear layer and M-Force™ Enhanced Urethane finish ensure performance under heavy commercial traffic. The adhesive-free construction works over existing flooring and saves time and costs.

**Urban Patina** delivers a bit of mystery: its unusual mix of known species and organic inspired patterns provide hints of wood visuals without exactly replicating any specific type. Various textures ranging from linear to hardscraped are available in an easy-to-install 7" x 48" size.

- Commercial grade wear layer and M-Force<sup>™</sup> Enhanced Urethane finish
- Uniclic® locking system for fast, adhesive-free installation
- Four-sided locking system prevents plank separation ensuring a tight fit
- Installs on slabs with up to 95% RH and contains added antimicrobial
- More forgiving over uneven subfloors and is move-in ready
- Contains 30% recycled content
- FloorScore® certified

# **Color Effects**

Solid, all loop textured tile available in 48 colors. Select colors also available as 12x36 plank. Install as a border, inset or accent tile.



# EcoFlex<sup>™</sup> ICT carpet tile backing



EcoFlex<sup>TM</sup> ICT is a premium vinyl modular backing system containing a minimum of 35% recycled content. With over 15 years in the marketplace, its ultra dense construction is engineered to offer superior performance while giving greater cushioning properties.



### PERFORMANCE

- Unsurpassed dimensional stability – no growing or shrinking
- Constructed with an ultra dense five layer cushion backing system
- Main body of tile provides an effective moisture barrier (not applicable at the seams)
- Tiles are impervious to moisture damage from spills and water extraction cleaning
- Construction features superior tuft bind that is highly resistant to edge ravel
- Proven performance for over 15 years



### BUDGET

 Superior construction offers reliability for the life of your installation



### SUSTAINABILITY

- EcoFlex ICT contains 35% minimum pre consumer recycled content by total weight\*
- Recyclable through Mohawk's ReCover program
- EcoFlex ICT may contribute to or comply with LEED® credits MR 4.0, IEQ 4.3 and Innovation credit for NSF 140
- CRI Green Label Plus certified
- Free of EPA phthalates of concern

- Certified at the Gold Level in accordance with NSF/ANSI 140 the Sustainability Assessment for Carpet
- NSF/ ANSI 140 Platinum level version available with a minimum of 10% post-consumer recycled content



### SERVICE

 Engineered performance for an overall better after sales service experience

<sup>\*</sup> Recycled content claim third party verified by UL (Underwriters Laboratory)

# EcoFlex<sup>™</sup> NXT AIR

carpet tile backing

EcoFlex<sup>™</sup> NXT AIR is a custom option for the Sense of Space collection and requires a minimum order of 500 sq. yds. and 10% overage.

Primary Backing
Fiberglass Scrim
Pre-Coat Polymer
Polyolefin Thermoplastics Polymer
PET Cushion

Pet tile,
und reduction and
orporates an average of

The next evolution in cushion backed carpet tile,

EcoFlex™ NXT AIR offers substantial sound reduction and
enhanced comfort under foot. It also incorporates an average of
50% recycled content (pre- and post-consumer) by total product weight.



## PERFORMANCE

- Provides permanent tile dimensional stability
- Tiles are impervious to moisture damage from spills and water extraction cleaning
- Main body of tile provides an effective moisture barrier (not applicable at the seams)
- Noise Reduction Coefficient is
   0.30 carpet tiles should reduce sound by 30%
- Impact Insulation Class 70 our product is more than 2x better in reducing sound transmission than hard surfaces and 40% better than standard carpet
- Construction features superior tuft bind that is highly resistant to edge ravel

- Provides additional thermal resistance (R-Value) reducing HVAC workload and cost
- Increased load deflection reduces physical stress and provides comfort under foot - the perfect solution for today's sit/stand work environments and high traffic areas
- Reduces the risk of injuries in the event of a slip or fall - a common concern in healthcare and assisted living facilities



#### SUSTAINABILITY

- Contains no plasticizers
- PET Cushion layer of EcoFlex NXT AIR is 95% post consumer recycled content.
- Finished product contains a total of 38% pre consumer and 12%

- post consumer recycled content or 50% total recycled content by total product weight
- Certified NSF/ ANSI 140 Platinum with a minimum of 10% post consumer recycled content
- EcoFlex NXT AIR may contribute to or comply with LEED® credits MR 4.0
- CRI Green Label Plus certified
- Mohawk Group is leading the entire manufacturing sector in the Living Building Challenge™ Declare program



### SERVICE

- Engineered performance for an overall better after sales service experience
- Contact your sales representative for more information

<sup>\*</sup> Recycled content claim third party verified by UL (Underwriters Laboratory)

| ] [ | Brand                           | Durkan                                 |   | Brand                    | Durkan                            |  |  |
|-----|---------------------------------|--|---|--------------------------|-----------------------------------|--|--|
| .   | Style Name / Number             | Classic Form / MD011                   | 4   | Style Name / Number      | Modern Functional / MD012         |  |  |
| П   | Construction                    | Tufted                                 | 7   | Construction             | Tufted                            |  |  |
|     | Surface Appearance              | Textured Patterned Loop                | B√  | Surface Appearance       | Textured Patterned Loop           |  |  |
|     | Gauge                           | 1/12" (47.00 rows per 10 cm)           | 24  | Gauge                    | 1/12" (47.00 rows per 10 cm)      |  |  |
|     | Dye Method                      | Solution Dyed                          |   | Dye Method               | Solution Dyed                     |  |  |
|     | Fiber Type                      | Colorstrand® SD Nylon                  |   | Fiber Type               | Colorstrand® SD Nylon             |  |  |
|     | Stain Release Technology        | Sentry Plus Stain Protection           |   | Stain Release Technology | Sentry Plus Stain Protection      |  |  |
|     | Soil Release Technology         | Sentry Soil Protection                 |   | Soil Release Technology  | Sentry Soil Protection            |  |  |
|     | Backing Material                | EcoFlex ICT                            |   | Backing Material         | EcoFlex ICT                       |  |  |
|     | Indoor Air Quality              | Green Label Plus Certified # 1098      |   | Indoor Air Quality       | Green Label Plus Certified # 1098 |  |  |
|     | NSF 140                         | Gold                                   |   | NSF 140                  | Gold                              |  |  |
|     | Size                            | 24" x 24" (.6096 m x .6096 m)          |   | Size                     | 24" x 24" (.6096 m x .6096 m)     |  |  |
|     | Installation Method             | Quarter Turn / Brick Ashlar /          |   | Installation Method      | Quarter Turn / Brick Ashlar /     |  |  |
|     |                                 | Vertical Ashlar / Monolithic /         |   |                          | Vertical Ashlar / Monolithic /    |  |  |
|     |                                 | Multi Directional                      |   |                          | Multi Directional                 |  |  |
|     | Flammability                    | ASTM E 648 Class 1 (Glue Down)         |   | Flammability             | ASTM E 648 Class 1 (Glue Down)    |  |  |
|     | Smoke Density                   | ASTM E 662 Less than 450               |   | Smoke Density            | ASTM E 662 Less than 450          |  |  |
|     | Static Propensity               | AATCC - 134 Under 3.5 KV               |   | Static Propensity        | AATCC - 134 Under 3.5 KV          |  |  |
|     | Warranties: Lifetime Limited (  | Carpet Tile Warranty, Lifetime Limited | Warranties: Lifetime Limited Carpet Tile Warranty, Lifetime Limited |                          |                                   |  |  |
|     | Colorfastness to Light, 10 Year | r Limited Colorfastness to             | Colorfastness to Light, 10 Year Limited Colorfastness to            |                          |                                   |  |  |
|     | Atmospheric Contaminants, 1     | 0 Year Stain Warranty, Lifetime Static | Atmospheric Contaminants, 10 Year Stain Warranty, Lifetime Static   |                          |                                   |  |  |

| ľ | Brand   | Durkan                                 |  |  |  |  |  |  |
|---|---|--|--|--|--|--|--|--|
| ı | Style Name / Number   | Elegantly Smart / MD013                |  |  |  |  |  |  |
| ı | Construction  | Tufted                                 |  |  |  |  |  |  |
| ı | Surface Appearance  | Textured Patterned Loop                |  |  |  |  |  |  |
| ı | Gauge   | 1/12" (47.00 rows per 10 cm)           |  |  |  |  |  |  |
| ı | Dye Method  | Solution Dyed                          |  |  |  |  |  |  |
| ı | Fiber Type  | Colorstrand® SD Nylon                  |  |  |  |  |  |  |
| ı | Stain Release Technology  | Sentry Plus Stain Protection           |  |  |  |  |  |  |
| ı | Soil Release Technology   | Sentry Soil Protection                 |  |  |  |  |  |  |
| ı | Backing Material  | EcoFlex ICT                            |  |  |  |  |  |  |
| ı | Indoor Air Quality  | Green Label Plus Certified # 1098      |  |  |  |  |  |  |
| ı | NSF 140   | Gold                                   |  |  |  |  |  |  |
| ı | Size  | 24" x 24" (.6096 m x .6096 m)          |  |  |  |  |  |  |
| ı | Installation Method   | Quarter Turn / Brick Ashlar /          |  |  |  |  |  |  |
| ı |   | Vertical Ashlar / Monolithic /         |  |  |  |  |  |  |
| ı |   | Multi Directional                      |  |  |  |  |  |  |
| ı | Flammability  | ASTM E 648 Class 1 (Glue Down)         |  |  |  |  |  |  |
| ı | Smoke Density   | ASTM E 662 Less than 450               |  |  |  |  |  |  |
| ı | Static Propensity   | AATCC - 134 Under 3.5 KV               |  |  |  |  |  |  |
| ı | Warranties: Lifetime Limited (                                    | Carpet Tile Warranty, Lifetime Limited |  |  |  |  |  |  |
| ı | Colorfastness to Light, 10 Yea                                    | r Limited Colorfastness to             |  |  |  |  |  |  |
| ı | Atmospheric Contaminants, 10 Year Stain Warranty, Lifetime Statio |  |  |  |  |  |  |  |

|        | Brand                           | Durkan                                 |  |  |  |  |
|--------|---------------------------------|--|--|--|--|--|
| _      | Style Name / Number             | Stately Stylish / MD014                |  |  |  |  |
| 7      | Construction                    | Tufted                                 |  |  |  |  |
| 24BY24 | Surface Appearance              | Textured Patterned Loop                |  |  |  |  |
| 2 4    | Gauge                           | 1/12" (47.00 rows per 10 cm)           |  |  |  |  |
|        | Dye Method                      | Solution Dyed                          |  |  |  |  |
|        | Fiber Type                      | Colorstrand® SD Nylon                  |  |  |  |  |
|        | Stain Release Technology        | Sentry Plus Stain Protection           |  |  |  |  |
|        | Soil Release Technology         | Sentry Soil Protection                 |  |  |  |  |
|        | Backing Material                | EcoFlex ICT                            |  |  |  |  |
|        | Indoor Air Quality              | Green Label Plus Certified # 1098      |  |  |  |  |
|        | NSF 140                         | Gold                                   |  |  |  |  |
|        | Size                            | 24" x 24" (.6096 m x .6096 m)          |  |  |  |  |
|        | Installation Method             | Quarter Turn / Brick Ashlar /          |  |  |  |  |
|        |                                 | Vertical Ashlar / Monolithic /         |  |  |  |  |
|        |                                 | Multi Directional                      |  |  |  |  |
|        | Flammability                    | ASTM E 648 Class 1 (Glue Down)         |  |  |  |  |
|        | Smoke Density                   | ASTM E 662 Less than 450               |  |  |  |  |
|        | Static Propensity               | AATCC - 134 Under 3.5 KV               |  |  |  |  |
|        | Warranties: Lifetime Limited (  | Carpet Tile Warranty, Lifetime Limited |  |  |  |  |
|        | Colorfastness to Light, 10 Year | r Limited Colorfastness to             |  |  |  |  |
|        | A. 1 . 0                        | 0.1/ 0/ 1.1/ / 1.1/ / 0/ /             |  |  |  |  |

Atmospheric Contaminants, 10 Year Stain Warranty, Lifetime Static

Installation Instructions:

| Monolithic   | Quarter Turn                        | Brick Ashlar | Vert. Ashlar | Multi-Directional |  |  |  |  |
|--------------|-------------------------------------|--------------|--------------|-------------------|--|--|--|--|
| <b>†</b> † † | $\uparrow$ $\rightarrow$ $\uparrow$ | 1 1 1        |              | ↑ ↓ ←             |  |  |  |  |
| 1 1 1        | → ↑ →                               | 1 1 1        |              | →   ↑   →         |  |  |  |  |
| 1 1 1        | ↑ → ↑                               | 1 1 1        |              | ← → ↓             |  |  |  |  |



Mohawk Industries, Inc. warrants its adhesives for the life of the original installation only when a Mohawk Industries style (product) is installed. Mohawk's floor preparation procedures must be followed to ensure that the substrate has been prepared properly. Failure to use Mohawk Industries adhesives or to follow Mohawk's floor preparation procedures will void all lifetime adhesive warranties. Please contact your local Sales Representative for installation guidelines.

These patterns contain inherent characteristics which may result in pattern run off and/or pattern appearance variations at the seams or tile edges (darker or lighter pattern lines). These characteristics are inherent in the patterns and are not manufacturing defects. Consideration to these characteristics should be given when selecting an installation method.

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to prevent premature or accelerated wear. Walk-off tiles from the Moving Along Collection are recommended at entryways to reduce soiling.

Mohawk Group is providing this architect folder for the purpose of promoting our commercial business. This folder and its samples shall remain the property of Mohawk Group. Color may vary from dye lot to dye lot. Substitution of material may be made due to improved technology, supply limitations or other factors. The performance of this product is not affected by such variations.

For current and complete specifications please visit durkan.com











| Brand  | Defining Vision / MD015<br>Tufted<br>Textured Patterned Loop<br>1/12" (47.00 rows per 10 cm)<br>Solution Dyed                        | 24BY24 | Brand  | Sleek Find / MD016<br>Tufted<br>Textured Patterned Loop<br>1/12" (47.00 rows per 10 cm)<br>Solution Dyed                             |
|--|--|--------|--|--|
| Stain Release Technology<br>Soil Release Technology<br>Backing Material<br>Indoor Air Quality<br>NSF 140 | Sentry Plus Stain Protection Sentry Soil Protection EcoFlex ICT Green Label Plus Certified # 1098 Gold 24" x 24" (.6096 m x .6096 m) |        | Stain Release Technology<br>Soil Release Technology<br>Backing Material<br>Indoor Air Quality<br>NSF 140 | Sentry Plus Stain Protection Sentry Soil Protection EcoFlex ICT Green Label Plus Certified # 1098 Gold 24" x 24" (.6096 m x .6096 m) |
| Smoke Density<br>Static Propensity<br>Warranties: Lifetime Limited (<br>Colorfastness to Light, 10 Yea   | AATCC - 134 Under 3.5 KV<br>Carpet Tile Warranty, Lifetime Limited   |        | Smoke Density<br>Static Propensity<br>Warranties: Lifetime Limited (<br>Colorfastness to Light, 10 Yea   | AATCC - 134 Under 3.5 KV<br>Carpet Tile Warranty, Lifetime Limited   |

For Color Effects and LVT spec information, visit our website at durkan.com.

#### Installation Instructions:

24BY24

| Monolithic |   |   | Quarter Turn Bi |          |          | Brick Ashlar |            |   | Vert. Ashlar |            |  | Multi-Directional |          |          |  |  |
|------------|---|---|-----------------|----------|----------|--------------|------------|---|--------------|------------|--|-------------------|----------|----------|--|--|
| Ť          | t | 1 | Ť               | -        | 1        |              | † † †      | t |              | + 1        |  | 1                 | ļ        | -        |  |  |
| 1          | 1 | 1 | -               | 1        | <b>→</b> |              | † †        | 1 | H            | <u>†</u> † |  | +                 | t        | <b>→</b> |  |  |
| 1          | 1 | 1 | 1               | <b>→</b> | 1        |              | <b>1</b> 1 | 1 | H            | <u>†</u> † |  | 1                 | <b>→</b> | ļ        |  |  |



Mohawk Industries, Inc. warrants its adhesives for the life of the original installation only when a Mohawk Industries style (product) is installed. Mohawk's floor preparation procedures must be followed to ensure that the substrate has been prepared properly. Failure to use Mohawk Industries adhesives or to follow Mohawk's floor preparation procedures will void all lifetime adhesive warranties. Please contact your local Sales Representative for installation guidelines.

These patterns contain inherent characteristics which may result in pattern run off and/or pattern appearance variations at the seams or tile edges (darker or lighter pattern lines). These characteristics are inherent in the patterns and are not manufacturing defects. Consideration to these characteristics should be given when selecting an installation method.

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to prevent premature or accelerated wear. Walk-off tiles from the Moving Along Collection are recommended at entryways to reduce soiling.

Mohawk Group is providing this architect folder for the purpose of promoting our commercial business. This folder and its samples shall remain the property of Mohawk Group. Color may vary from dye lot to dye lot. Substitution of material may be made due to improved technology, supply limitations or other factors. The performance of this product is not affected by such variations.

For current and complete specifications please visit durkan.com









