

shaw hard surface

 \diamond

DESIGNESOUD





product specifications

Installation:	direct glue	
Style info:	surface 0515V strand 0516V	
Wear layer:	.02 in 20 mm	
Overall thickness:	.98 in 2.5 mm	
Nominal dimensions:	18"x 36" 45.72 cm x 91.44 cm	
Finish:	Exoguard™	
Warranty:	10 year commercial wear warranty	

CEMENTED ELEMENTS

Concrete characteristics. Linear stone. These are the subtle visuals of Surface and Strand, two 18x36 resilient designs. Mix styles and add scale. Bring an air of composed balance to architectural spaces. The 20 mil wear layer is perfect for heavy commercial traffic and the improved surface finish minimizes scuffing, for enhanced performance and durability. **DESIGN IS SOLID**

	coordinating WALL BAS
	8
15500 pitch	00580 slate
15595 sediment	00580 slate 00790 flint 00770 earthen
15740 soil	00770 earthen
the second s	
15506 boulder	00760 clay
15518 cement	00560 greige
15530 gravel	00750 cement
15111 granite	00780 agate
15155 natural	00780 agate
	Sol So agato
15114 cashmere	00500 rock
15515 quartz	00120 sterling
STRAND	COORDINATING WALL BASE
16515 chalk	00120 sterling
16516 dune	00170 suede
16115 wool	00500 rock
16761 clay	00770 earthen
16530 pebble	00750 cement
16595 silt	00580 slate

shaw hard surface

For more information on **Surface and Strand**, contact your local Shaw Contract Group representative, visit us at shawhardsurface.com or call 877-502-SHAW.