

iD inspiration 55

Datasheet

Classification	Norm	Tarkett Value
Product type	EN ISO 10582	Heterogeneous poly(vinyl chloride) floor coverings
Domestic classification	EN ISO 10874	23 Heavy
Commercial classification	EN ISO 10874	33 Heavy
Industrial classification	EN ISO 10874	42 General
Technical Characteristics	Norm	Tarkett Value
Total thickness	EN ISO 24346	2,50 mm
Wear layer thickness	EN ISO 24340	0,55 mm
Total weight	EN ISO 23997	3850 g/m ²
Binder content	EN ISO 10582	Type I
Surface treatment		TEKTANIUM ®
Embossing in Register		Yes
Bevelled edges		No bevel 4 sides
Installation method		Glue-Down
Performance for CE Marking	Norm	Tarkett Value
Declaration of Performance #	EN 14041	0132-0084-DoP-2020-03
Technical Performance	Norm	Tarkett Value
Dimensional stability	EN ISO 23999	Average measured value : ≤ 0.10 %
Curl resultant to heat	EN ISO 23999	≤ 2 mm
Reaction to fire	EN 13501-1	Bfl-s1
Residual indentation	EN ISO 24343-1	≤ 0,05 mm
Furniture leg	EN ISO 16581	No damage
Castor chair	EN ISO 4918	No damage
Impact sound reduction - ΔLw	EN ISO 717-2	3 dB
Reduction of in-room impact noise	NF S31-074	Class C (≤ 85 dB)
Thermal resistance	EN ISO 10456	0,02 m ² •K/W
Colour fastness to light	EN ISO 105-B02	≥ 6
Chemical resistance	EN ISO 26987	Excellent Resistance
Slip resistance	DIN 51130	R9 R10
Slip resistance	EN 13893	Class DS (μ ≥ 0,30)
Static Electrical Propensity	EN 1815	Antistatic (≤ 2 kV)
Underfloor heating		Suitable (maximum 27°C)
Sustainability performances	Norm	Tarkett Value
Recycled content		39,5 %
Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3)		7,71 kg CO ₂ eq /m ²
Total VOC Emissions	EN 16516	Platinum (≤ 10 μg/m ³)
Dimensions and designs		
Plank	Plank 1200x200mm - 15 planks=3,6 m ² /box - 55 boxes/pallet Plank 1200 x 285mm - 11 planks=3,76 m ² /box - 54 boxes/pallet Plank 250 x 1500 mm - 10 planks=3,75 m ² /box - 56 boxes/pallet	
Tile	Tile 50 x 50 cm / 19,68" x 19,68" - 15 tiles=3,75 m ² /box - 52 boxes/pallet Tile 666 x 666 mm - 8 tiles=3,55 m ² /box - 40 boxes/pallet Tile 666 x 333mm - 16 tiles=3,55 m ² /box - 40 boxes/pallet Tile 500 x 1000 mm - 7 tiles=3,5 m ² /box - 54 boxes/pallet	
Number of designs available	100	

Embossing in register : on Authentics references

Slip resistance DIN : R9/R10 depending on embossing



The above information is subject to modification for the benefit of further improvement (07/09/2022). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed.

Please contact Tarkett at the address shown for the instructions.