

Mohawk Group

C0059 Metal

Hot and Heavy Collection



DESIGN

Product Type: Floating LVT

Overall Thickness: 5 mm (.2")

Wear Layer: 20 mil (0.5 mm)

Finish: M-Force Ultra

Size: 457.2 mm x 914.4 mm (actual) 18"W x 36"L (nominal)

Square Feet Per Carton: 18 sf/ctn

Pieces Per Carton: 4 pieces/ctn

Pounds per carton: 34 lbs/ctn

Installation Method: Loose Lay with Perimeter Glue or Full Spread

Recommended Adhesive: M95.0 Resilient Flooring Adhesive, M99 Resilient

Flooring Adhesive, or M700 Adhesive

Commercial Grade Loose Lay Enhanced Resilient

PERFORMANCE

Construction: ASTM F1700 - Class III, Type A - Smooth, Type B -Classification: **Embossed** ASTM F2055 - Passes - 0.010 in. max Squareness: ASTM F2055 - Passes - ±0.016 in. per linear foot Size and Tolerance: ASTM F386 - Passes - as specified ±0.005 in. (±0.13 Thickness: mm) Flexibility: ASTM F137 - Passes - \leq 1.0 in., no cracks or breaks ASTM F2199 - Passes - ≤ 0.024 in. per linear foot Dimensional Stability: Residual Indentation: ASTM F1914 - Passes - Average less than 8% Resistance To Chemicals: ASTM F925 - Passes - No Change or Slight Change Resistance To Light: ASTM F1515 - Passes - ∆E ≤ 8



132 Golden Yellow Quickship Available



258 Viva Gold Quickship Available



268 My Precious Quickship Available



353 Rave Red Quickship Available



464 Vogue Violet Quickship Available



525 Freshwater Blue Quickship Available



556 Tempo Teal Quickship Available



585 Blue Steel Quickship Available



631 Lemon Lime Quickship Available

SUSTAINABILITY

Resistance To Heat: Critical Radiant Flux:

Certification: FloorScore® certified

Certification Detail: Minimum 8% bio-based renewable resource content by total product weight

ASTM F1514 - Passes - ∆E ≤ 8

ASTM E648 - Passes - ≥ 0.45 watts/cm2, Class 1

SERVICE

Warranties: Limited 10 Year Commercial



Hot and Heavy Collection







929 Proper Gray Quickship Available



959 So Fetch Quickship Available