

With thoughtful consideration for design, performance and a sustainable path, we've crafted a foundational collection of luxury vinyl tiles that fit perfectly into the Interface flooring systems.

Level Set Textured Woodgrains is a selection of 25cm x 1m Skinny Planks™ in classic wood looks and a highly textured finish inspired by distressed, reclaimed and exposed finishes. Textured Woodgrains is offered in a range of earthy neutrals from light to dark.

It's not only a perfect match to our Skinny Planks and square carpet tiles, it is also a perfect fit in terms of thickness. This means you can easily install our resilient and soft flooring to create an integrated floor or inset rug, and move effortlessly from surface to surface without transition strips.

We design all our products with the ability to feed ReEntry®, our reclamation program. And, of course, like all of our products made around the world, the Level Set Collection is carbon neutral--just some of the many steps we take toward creating a climate fit for life. Join the #ClimateTakeBack movement.











Specifications

Product Number A004

Product Construction High Performance Luxury Vinyl Tile
Class / ASTM F1700 Class III Printed Vinyl Plank

Class / ASTM F1700 Class III Printed Vinyl I Wear Layer Thickness 22 mil

Total Thickness 4.5 mm

Backing Class Commercial Grade
Finish Ceramor[™] Coating

Nominal Dimensions 25cm x 1m (9.845 in x 39.38 in)

Performance

IIC Sound Rating (ASTM E492-09) 57 IIC

Slip Resistance (ASTM D2047) > 0.55 wet/dry, ADA Compliant

Static Load Limit (ASTM F970) 1500 psi Flexibility (ASTM F137) Passes Resistance to Heat (ASTM F1514) Passes Resistance to Light (ASTM F1515) Passes Radiant Flux (ASTM E648) Class I Smoke Density (ASTM E662) Passes, ≤450

Size & Squareness (ASTM F2055) Passes, +/- 0.016 in. per linear foot

Thickness (ASTM F386) Passes
Dimensional Stability (ASTM F2199) Passes
Residual Indentation (ASTM F1914) Passes
Resistance to Chemicals (ASTM F925) Passes

Environmental

Indoor Air Quality FloorScore®/CDPH 01350 Certified for

low-VOC emissions

Material Composition Free of Ortho Phthalates, Added Formaldehyde and

Heavy Metal Stabilizers

Ingredients & Life Cycle Impacts
Carbon Footprint
Sustainability Assessment
Carbon Footprint
Sustainability Assessment
Sustainability Assessment
Sustainability Assessment
Sustainability Assessment
Sustainability Assessment

NSF/ANSI 332, Meets Certification Guidelines Contributes to IEQ: Low Emitting Materials; M&R:

EPD and EPR

End of Life Fully Recyclable LVT to Carpet Tile Backing

Packaging

LEED v4

 Square Feet per Carton
 26.91 sq. ft. (2.5 m²)

 Pieces per Carton
 10

 Weight per Carton
 40 lbs (18 kg)

 Cartons per Pallet
 40

 Pallets per Truckload
 20

Technical Information

 Installation
 See Interface LVT Installation Guidelines online

 Maintenance
 See Interface LVT Maintenance Guidelines online

 Reclamation
 Recyclable through ReEntry® - Call

1.888.733.6873 (U.S.) / 1.866.398.3191 (Canada)

Warranty 15 Year Limited Commercial Warranty

Installation Methods Ashlar, Herringbone



All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see our full LVT product disclaimer @ interface.com.

Textured Woodgrains Colorline



A00401 DISTRESSED WALNUT



A00402 DISTRESSED CASHEW



A00403 DISTRESSED HICKORY



A00404 DISTRESSED BLACK WALNUT



A00405 GREY DUNE



A00406 ANTIQUE LIGHT OAK



A00407 WHITE WASH



A00408 ANTIQUE GRAY OAK



A00409 ASH WALNUT



A00410 SILVER WALNUT



A00411 DARK WALNUT



A00412 RECLAIMED HICKORY



A00415 ANTIQUE OAK



A00416 ANTIQUE DARK OAK



A00417 SILVER DUNE



A00418 CHARCOAL DUNE







Integrated System.

Say goodbye to transition strips and doubling up. Our modular resilient floorings are made to work as a system with our modular carpet. The compatible size and height of our products allows you to integrate modular carpet for an inset rug or an adjacent field – no transition strip required. You'll avoid doubling up on materials and save money.

Real Flexibility.

Create a unique look that lasts. Interface modular resilient LVT makes it easy to extend the life of your floor. From simple maintenance like damp mopping to selectively replacing damaged tiles, your flooring investment will stand the test of time - beautifully and effortlessly.

Circular System.

Keep flooring out of the landfill. Our modular resilient LVT is produced with a controlled material stream so it can be reclaimed and recycled into our GlasBac®RE recycled content backing through our ReEntry® program.

Noise Reduction.

Silence distractions. Interface is helping create +Positive spaces™ with our LVT with Sound Choice backing. Sound Choice is a specially formulated backing developed for superior noise reduction, offering you best-in-class performance for reduced impact sound and floor to floor sound transmission.



High Performance from Top to Bottom.

- 1. Ceramor™ Coating. Minimizes everyday scratching and scuffing.
- 2. Wear Layer. High quality layer enabling 15 years of resilience and performance.
- **3.** *Print Film.* Provides outstanding visuals of natural materials and Interface innovative designs.
- **4.** Core Sheet. Creates a thickness for a stronger core and reduces telegraphing from beneath.
- 5. Fiberglass. Adds dimensional stability and controlled flexibility.
- **6.** Core Sheet. Creates a thickness for a stronger core and reduces telegraphing from beneath.
- **7.** Sound Choice[™]. Provides comfort and superior acoustic performance.







Third Party Certification.

Carbon Neutral Floors. All Interface flooring sold globally is third party verified carbon neutral. We've taken a holistic approach to achieve carbon neutrality, first through reducing the carbon footprint of our products and then using carbon offsets for the remainder.

Environmental Product Declaration (EPD). Interface LVT products are covered by an EPD. An EPD provides a comprehensive statement of product ingredients and environmental impacts based upon life cycle assessment performed to ISO standards.

Sustainable Assessment. Interface LVT meets the certification standards of the NSF/ANSI 332 Sustainability Assessment for Resilient Floor Coverings. This standard evaluates the environmental impact of resilient floor covering for its entire lifecycle.

Indoor Air Quality. All Interface modular flooring products meet the highest standards for indoor air quality. Interface LVT is FloorScore® Certified, assuring very low emissions of VOCs.







Printed on 50% post consumer waste (PCW) fiber manufactured using wind power.

We have tried our very best to accurately represent product colors. However, due to the nature of printed materials, color of actual products may vary slightly. Please request a sample to see actual product color.

www.interface.com

United States Headquarters

1503 Orchard Hill Road LaGrange, GA 30240 1.800.634.6032

Canadian Headquarters

233 Lahr Drive Belleville, ON K8N 5S2 1.800.267.2149 ext.52128

Brazilian Headquarters

Rua Surubim, 577 - Conjuntos 73/74 7° Andar 04571-050 - São Paulo - SP + 55 11 2196 0900

Latin American Headquarters

Montes Urales # 415 Piso 6 Col. Lomas de Chapultepec México City, D.F. 11000 Mexico + 52 55 6395 5100

+ 32 33 0393 3100





Climate change is undeniable. And reversible. Our mission is to prove it. Join the #ClimateTakeBack and help create a climate fit for life.