

iD Tilt

LUXURY VINYL TILES

New
additions

Interdeco™

iD Tilt is Tarkett's floating floorcovering solution designed for commercial and industrial applications. To extend this collection, 4 new designs have been added.

GRANITE

Specially designed for large surfaces, Granite is the ideal solution to mask dirt and dust in high traffic areas. It is the embodiment of durability and strength.



Granite Basalt
4697015

91,44 x 91,44 cm

TARMAC

Tarmac is perfect for zoning or setting contrasts. The Black pattern, that reminds of Obsidian, is also suitable for adding luxury to the high traffic commercial areas.



Tarmac Black
24750004

45,72 x 45,72 cm

WOVEN

Woven finishes the high traffic interior with a contemporary warming ambience. Woven Canvas portrays the flexibility and resistance of the product itself, whereas Linen is a modern Woven Pattern in a natural Linen Color.



Woven Linen

24750005

45,72 x 45,72 cm

Woven Canvas

24750006

45,72 x 45,72 cm

iD TILT

TECHNICAL DATA

Certification & classification	Standards	iD Tilt
Type of floor covering	EN ISO 10582	Modular heterogeneous product with interlocking connection
CE certification	EN 14041	Yes
Classification	EN ISO 10874 (EN 685)	Commercial: 34 Industrial: 43
Technical characteristics		
Total thickness	EN ISO 24346	5,0 mm
Wear layer thickness	EN ISO 24340	0,70 mm
Total weight	EN ISO 23997	7400 g/m ²
Wear layer binder content	EN ISO 10582	Type I
Dimensions	EN ISO 24342 - EN 427 Tiles*	91,44 x 91,44 cm (Granite) 3 tiles/box (= 2,51 m ² - 18,56 kg) 45,72 x 45,72 cm (Concrete - Tarmac - Woven) 10 tiles/box (= 2,09 m ² - 15,47 kg)
Surface treatment (PUR)		Yes, TopCleanXP™
Technical performances		
Dimensional stability	EN ISO 23999 - EN 434	< 0,15 %
Reaction to fire	EN 13501-1	B _{fl} -s1 over concrete substrate
Residual indentation	EN ISO 24343-1 - EN 433	< 0.10 mm
Furniture leg	ISO 16581 - EN 424	No damage
Castor chair	ISO 4918 - EN 425	No damage
Curly resultant to heat	ISO 23999 - EN 434	≤ 2 mm
Impact sound reduction	EN ISO 717-2	ΔL _w = 6 dB
Thermal resistance	EN ISO 10456	approx. 0,05 m ² K/W
Light fastness	EN ISO 105-B02	≥ 6
Slip resistance	EN 13893 DIN 51130	μ ≥ 0,30 DS R9
Electrical properties	EN 1815 EN 1081	< 2 kV on concrete R1 > 10 ⁹ Ω
Resistance to chemicals	EN ISO 26987 - EN 423	Resistance
Environmental TAG		
VOC emission	ISO 16000-9	< 100 μg/m ³
Recycled content		0%
Recyclable		100%
Plasticizer		100% Phtalate-free

The above information is subject to modification for the benefit of further improvement. (01/17).

Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for these instructions.

*The 2 formats are not interconnectable.

CUSTOMS TARIFF : 4820 5000 00



According to Classification ISO 10874

