

Horizon's Edge  
Collection



 Interdeco™

 DURKAN




# HORIZON'S EDGE

COLLECTION

5 styles, infinite design flexibility, effortless installation and ease of maintenance. Mix and match coordinating patterns, styles and colors to create your own unique look or define a particular space.



Equatorial Rim  
927 Shale



Terraforming  
927 Shale



Before Dawn  
927 Shale



Heavy Earth  
927 Shale



Intelligence  
7959 Cameleon Mixer





# Global Entry Collection

Resilient Tile: Global Entry, Sereno, color 663

 Mohawk Group

Global Entry features hardwood species from across the world in a collection of contemporary colors and realistic wood textures. The commercial grade wear layer and M-Force™ Enhanced Urethane finish ensures product performance through the life of the installation.

**Sereno** is a tranquil approach to luxury vinyl tile, featuring a pattern that blurs the line between contemporary concrete and serene sandstone visuals. Colors are inspired by natural materials like clay and sand, evoking feelings of calm in any space. The directional pattern works with a variety of installation methods, including herringbone and right angle designs which take advantage of the large rectangular format.

**Shikumen** elevates the cold, industrial feel of traditional concrete to a new generation of luxury vinyl tile. The all over pattern plays homage to ancient frescoes, but offers the raw edge of a repurposed building. The energetic visual offers a non-directional option in an 18" x 36" tile and hides wear better than solid concrete visuals.

- Wide range of visuals to accommodate a variety of end use segments and design schemes
- Updated 18" x 36" format
- M-Force™ Enhanced Urethane finish for superior wear and scratch resistance
- 20 mil wear layer performs under commercial traffic
- No-polish maintenance reduces costs associated with long-term cleaning
- FloorScore® certified
- QuickShip available

# EcoFlex™ ICT

Modular backing



EcoFlex™ ICT is a premium vinyl modular backing system containing a minimum of 35% recycled content. With over 15 years in the marketplace, its ultra dense construction is engineered to offer superior performance while giving greater cushioning properties.



## PERFORMANCE

- Unsurpassed dimensional stability – no growing or shrinking
- Constructed with an ultra dense five layer cushion backing system
- Main body of tile provides an effective moisture barrier (not applicable at the seams)
- Tiles are impervious to moisture damage from spills and water extraction cleaning
- Construction features superior tuft bind that is highly resistant to edge ravel
- Proven performance for over 15 years



## BUDGET

- Superior construction offers reliability for the life of your installation



## SUSTAINABILITY

- EcoFlex ICT contains 35% minimum pre consumer recycled content by total weight\*
- Recyclable through Durkan's ReCover program
- EcoFlex ICT may contribute to or comply with LEED® credits MR 4.0, IEQ 4.3 and Innovation credit for NSF 140
- CRI Green Label Plus certified
- Free of EPA phthalates of concern



## SERVICE

- Certified at the Gold Level in accordance with NSF/ANSI 140 the Sustainability Assessment for Carpet
- NSF/ ANSI 140 Platinum level version available with a minimum of 10% post-consumer recycled content
- Engineered performance for an overall better after sales service experience

\* Recycled content claim third party verified by UL (Underwriters Laboratory)

# EcoFlex™ NXT AIR

carpet tile backing

EcoFlex™ NXT AIR is a custom option and requires a minimum order of 500 sq. yds. and 10% overage.



The next evolution in cushion backed carpet tile, EcoFlex™ NXT AIR offers substantial sound reduction and enhanced comfort under foot. It also incorporates an average of 50% recycled content (pre- and post-consumer) by total product weight.



## PERFORMANCE

- Provides permanent tile dimensional stability
- Tiles are impervious to moisture damage from spills and water extraction cleaning
- Main body of tile provides an effective moisture barrier (not applicable at the seams)
- Noise Reduction Coefficient is 0.30 - carpet tiles should reduce sound by 30%
- Impact Insulation Class 70 - our product is more than 2x better in reducing sound transmission than hard surfaces and 40% better than standard carpet
- Construction features superior tuft bind that is highly resistant to edge ravel



## SUSTAINABILITY

- Provides additional thermal resistance (R-Value) reducing HVAC workload and cost
- Increased load deflection reduces physical stress and provides comfort under foot - the perfect solution for today's sit/stand work environments and high traffic areas
- Reduces the risk of injuries in the event of a slip or fall - a common concern in healthcare and assisted living facilities
- Contains no plasticizers
- PET Cushion layer of EcoFlex NXT AIR is 95% post consumer recycled content.
- Finished product contains a total of 38% pre consumer and 12%



## SERVICE

- post consumer recycled content or 50% total recycled content by total product weight
- Certified NSF/ ANSI 140 Platinum with a minimum of 10% post consumer recycled content
- EcoFlex NXT AIR may contribute to or comply with LEED® credits MR 4.0
- CRI Green Label Plus certified
- Mohawk Group is leading the entire manufacturing sector in the Living Building Challenge™ Declare program
- Engineered performance for an overall better after sales service experience
- Contact your sales representative for more information

\* Recycled content claim third party verified by UL (Underwriters Laboratory)



# The Leader in Transparency and Red List Free Products

Durkan leads the building products industry in transparency with the largest selection of products with Declare Labels, Health Product Declarations (HPDs), and Environmental Product Declarations (EPDs). What’s more, we offer over 490 Red List Free Declared products.

## OUR COMMITMENT

As a Gaia sponsor of the International Living Future Institute (ILFI), we are committed to revolutionary programs that are redefining the green building movement. These include the ILFI’s Living Building Challenge and Declare programs.

Declare Labels are a ‘nutrition label’ for the building industry, providing ingredients, source and manufacturing locations. We offer you:

- The most products with Declare Labels
- The most Red List Free products

We have eliminated the mystery of product ingredients so you get total product transparency.\*

Example of a Durkan Declare Label



Durkan utilizes multiple platforms for disclosing our transparency information, including: Designer Pages, Mindful Materials and the Declare Database.”

\* Transparency documentation can be found at [www.durkan.com](http://www.durkan.com)


24BY24	Brand.....	<b>Durkan</b>
	Style Name / Number .....	<b>Equatorial Rim / MD047</b>
	Construction.....	Tufted
	Surface Appearance.....	Level Patterned Loop
	Gauge.....	1/12" (47.00 rows per 10 cm)
	Dye Method.....	Solution Dyed
	Fiber Type.....	Colorstrand® SD Nylon
	Stain Release Technology....	Sentry Plus Stain Protection
	Soil Release Technology.....	Sentry Soil Protection
	Backing Material.....	EcoFlex ICT
	Indoor Air Quality.....	Green Label Plus Certified # 1098
	NSF 140.....	Gold
	Size.....	24" x 24" (.6096 m x .6096 m)
	Installation Method.....	Monolithic / Vertical Ashlar / Brick Ashlar / Quarter Turn / Multi Directional
	Flammability.....	ASTM E 648 Class 1 (Glue Down)
	Smoke Density.....	ASTM E 662 Less than 450
	Static Propensity.....	AATCC - 134 Under 3.5 KV
	Warranties: Lifetime Limited Carpet Tile Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Stain Warranty, Lifetime Static	

24BY24	Brand.....	<b>Durkan</b>
	Style Name / Number .....	<b>Terraforming / MD048</b>
	Construction.....	Tufted
	Surface Appearance.....	Level Patterned Loop
	Gauge.....	1/12" (47.00 rows per 10 cm)
	Dye Method.....	Solution Dyed
	Fiber Type.....	Colorstrand® SD Nylon
	Stain Release Technology....	Sentry Plus Stain Protection
	Soil Release Technology.....	Sentry Soil Protection
	Backing Material.....	EcoFlex ICT
	Indoor Air Quality.....	Green Label Plus Certified # 1098
	NSF 140.....	Gold
	Size.....	24" x 24" (.6096 m x .6096 m)
	Installation Method.....	Monolithic / Vertical Ashlar / Brick Ashlar / Quarter Turn / Multi Directional
	Flammability.....	ASTM E 648 Class 1 (Glue Down)
	Smoke Density.....	ASTM E 662 Less than 450
	Static Propensity.....	AATCC - 134 Under 3.5 KV
	Warranties: Lifetime Limited Carpet Tile Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Stain Warranty, Lifetime Static	

24BY24	Brand.....	<b>Durkan</b>
	Style Name / Number .....	<b>Before Dawn / MD049</b>
	Construction.....	Tufted
	Surface Appearance.....	Level Patterned Loop
	Gauge.....	1/12" (47.00 rows per 10 cm)
	Dye Method.....	Solution Dyed
	Fiber Type.....	Colorstrand® SD Nylon
	Stain Release Technology....	Sentry Plus Stain Protection
	Soil Release Technology.....	Sentry Soil Protection
	Backing Material.....	EcoFlex ICT
	Indoor Air Quality.....	Green Label Plus Certified # 1098
	NSF 140.....	Gold
	Size.....	24" x 24" (.6096 m x .6096 m)
	Installation Method.....	Monolithic / Vertical Ashlar / Brick Ashlar / Quarter Turn / Multi Directional
	Flammability.....	ASTM E 648 Class 1 (Glue Down)
	Smoke Density.....	ASTM E 662 Less than 450
	Static Propensity.....	AATCC - 134 Under 3.5 KV
	Warranties: Lifetime Limited Carpet Tile Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Stain Warranty, Lifetime Static	

24BY24	Brand.....	<b>Durkan</b>
	Style Name / Number .....	<b>Heavy Earth / MD050</b>
	Construction.....	Tufted
	Surface Appearance.....	Level Patterned Loop
	Gauge.....	1/12" (47.00 rows per 10 cm)
	Dye Method.....	Solution Dyed
	Fiber Type.....	Colorstrand® SD Nylon
	Stain Release Technology....	Sentry Plus Stain Protection
	Soil Release Technology.....	Sentry Soil Protection
	Backing Material.....	EcoFlex ICT
	Indoor Air Quality.....	Green Label Plus Certified # 1098
	NSF 140.....	Gold
	Size.....	24" x 24" (.6096 m x .6096 m)
	Installation Method.....	Monolithic / Vertical Ashlar / Brick Ashlar / Quarter Turn / Multi Directional
	Flammability.....	ASTM E 648 Class 1 (Glue Down)
	Smoke Density.....	ASTM E 662 Less than 450
	Static Propensity.....	AATCC - 134 Under 3.5 KV
	Warranties: Lifetime Limited Carpet Tile Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Stain Warranty, Lifetime Static	

Installation Instructions:



Mohawk Industries, Inc. warrants its adhesives for the life of the original installation only when a Mohawk Industries style (product) is installed. Mohawk's floor preparation procedures must be followed to ensure that the substrate has been prepared properly. Failure to use Mohawk Industries adhesives or to follow Mohawk's floor preparation procedures will void all lifetime adhesive warranties. Please contact your local Sales Representative for installation guidelines.

**These patterns contain inherent characteristics which may result in pattern run off and/or pattern appearance variations at the seams or tile edges (darker or lighter pattern lines). These characteristics are inherent in the patterns and are not manufacturing defects. Consideration to these characteristics should be given when selecting an installation method.**

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to prevent premature or accelerated wear. Walk-off tiles from the Moving Along Collection are recommended at entryways to reduce soiling.

Mohawk Group is providing this architect folder for the purpose of promoting our commercial business. This folder and its samples shall remain the property of Mohawk Group. Color may vary from dye lot to dye lot. Substitution of material may be made due to improved technology, supply limitations or other factors. The performance of this product is not affected by such variations.

For current and complete specifications please visit [durkan.com](http://durkan.com)




24BY24

Brand.....	<b>Durkan</b>
Style Name / Number .....	<b>Intelligence / MD064</b>
Construction.....	Tufted
Surface Appearance.....	Textured Patterned Loop
Gauge .....	1/8" (31.50 rows per 10 cm)
Dye Method.....	Solution Dyed
Fiber Type .....	Colorstrand® SD Nylon
Stain Release Technology ....	Sentry Plus Stain Protection
Soil Release Technology.....	Sentry Soil Protection
Backing Material.....	EcoFlex ICT
Indoor Air Quality.....	Green Label Plus Certified # 1098
NSF 140.....	Gold
Size .....	24" x 24" (.6096 m x .6096 m)
Installation Method.....	Monolithic / Vertical Ashlar / Brick Ashlar / Quarter Turn
Flammability.....	ASTM E 648 Class 1 (Glue Down)
Smoke Density.....	ASTM E 662 Less than 450
Static Propensity .....	AATCC - 134 Under 3.5 KV
Warranties: Lifetime Limited Carpet Tile Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Stain Warranty, Lifetime Static	



For Sereno spec information, visit our website at [durkan.com](http://durkan.com).

Installation Instructions:



Mohawk Industries, Inc. warrants its adhesives for the life of the original installation only when a Mohawk Industries style (product) is installed. Mohawk's floor preparation procedures must be followed to ensure that the substrate has been prepared properly. Failure to use Mohawk Industries adhesives or to follow Mohawk's floor preparation procedures will void all lifetime adhesive warranties. Please contact your local Sales Representative for installation guidelines.

**These patterns contain inherent characteristics which may result in pattern run off and/or pattern appearance variations at the seams or tile edges (darker or lighter pattern lines). These characteristics are inherent in the patterns and are not manufacturing defects. Consideration to these characteristics should be given when selecting an installation method.**

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to prevent premature or accelerated wear. Walk-off tiles from the Moving Along Collection are recommended at entryways to reduce soiling.

Mohawk Group is providing this architect folder for the purpose of promoting our commercial business. This folder and its samples shall remain the property of Mohawk Group. Color may vary from dye lot to dye lot. Substitution of material may be made due to improved technology, supply limitations or other factors. The performance of this product is not affected by such variations.

**For current and complete specifications please visit [durkan.com](http://durkan.com)**



