



LORING WOODS



LORING WOODS Style Name

Style Number 54704 Broadloom Product Type Construction **Cut Pile Print**

Fiber Eco Solution Q® Nylon Print

Dye Method **Printed** Synthetic Primary Backing Classicbac Secondary Backing Traffic Rating Severe Protective Treatments R₂X

> U.S. Metric

Product Size 12 ft 3.66 m

Gauge 1/10 in 39.37 per 10 cm Stitches 26 per 10 cm 7 per in Finished Pile Thickness 0.095 in 2.41 mm

Average Density 3411 oz/yd3

Total Thickness 0.206 in 5.23 mm Tufted Weight 9 oz/yd² 305.2 g/m²

Pattern Repeat 3 ft W X 1,5 ft L 91.44 cm W X 45.72 cm L



Recommended Installation Methods

Direct Glue

Performance Testing

Pill Test Pass Class I Radiant Panel NBS Smoke

Less than 450 CRI Greenlabel Plus GLP8878

ADA Compliance >0.6, meets the recommended static coefficient of friction

for ADA walking surfaces and accessible routes

Warranties

Eco Solution Q Nylon (print base) Classicbac Twenty Year Commercial Limited Warranty

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

