



**DESIGN**

Product Type:	Floating LVT
Overall Thickness:	3.2 mm (.13")
Wear Layer:	12 mil (0.3 mm)
Finish:	Enhanced Urethane
Size:	150mm x 1235mm (actual) 6" x 48"L (nominal)
Square Feet Per Carton:	31.9 sf/ctn
Pieces Per Carton:	16 pieces/ctn
Pounds Per Carton:	47.41 lbs/ctn
Installation Method:	Floating LVT with Uniclic Locking System
Recommended Adhesive:	None Required
Underlayment:	Mohawk ActiveSound

**SUSTAINABILITY**

Certification:	FloorScore® certified
----------------	-----------------------

**PERFORMANCE**

Construction:	Light Commercial Grade Luxury Vinyl Tile
Classification:	ASTM F1700 - Class III, Type A - Smooth, Type B - Embossed
Squareness:	ASTM F2055 - Passes - 0.010 in. max
Size And Tolerance:	ASTM F2055 - Passes - ±0.016 in. per linear foot
Thickness:	ASTM F386 - Passes - as specified ±0.005 in. (±0.13 mm)
Flexibility:	ASTM F137 - Passes - ≤ 1.0 in., no cracks or breaks
Dimensional Stability:	ASTM F2199 - Passes - 0.15% max (0.020 in. per linear foot)
Residual Indentation:	ASTM F1914 - Passes - Average less than 8%
Resistance To Chemicals:	ASTM F925 - Passes - No Change
Resistance To Light:	ASTM F1515 - Passes - ΔE ≤ 8
Resistance To Heat:	ASTM F1514 - Passes - ΔE ≤ 8
Critical Radiant Flux:	ASTM E648 - Passes - ≥ 0.45 watts/cm <sup>2</sup> , Class 1
Smoke Density:	ASTM E662 - Passes - < 450

**SERVICE**

Warranties:	Limited 6 Year Commercial Warranty
-------------	------------------------------------



233  
Gally Gold  
Quickship Available



242  
Honeytone  
Quickship Available



258  
Realist  
Quickship Available



262  
Pier  
Quickship Available



717  
Winter White  
Quickship Available



822  
Blondie  
Quickship Available



857  
Woodridge  
Quickship Available



872  
Bombay  
Quickship Available



881  
Armoire  
Quickship Available



988  
Key-Note  
Quickship Available